Glaze

GENERAL SPECIFICATIONS

Overall Composition	80% PVC / 20% Polyester
Surface Composition	100% PVC (Phthalate Free)
Backing Composition	75% Polyester / 25% Cotton
Weight	36.0 oz. Per Linear Yard 795.8 gsm
Width	54”
Thickness	1.10 mm
Direction	Non-Directional

PERFORMANCE SPECIFICATIONS

Abrasion Resistance	100,000+ Double Rubs*	ASTM D4157-13
Stain Resistance	Yes, PFAS-free	
Bleach Resistance	Yes, 10% Dilution	
Breaking Strength	Warp: 67 / Fill: 78	ASTM D751-06(2011)
Coating Adhesion	Warp: 11.03 / Fill: 9.73	ASTM D751-06(2011)
Cold Crack	-20° F	CFFA-6a-2010
Colorfastness to Light	Class 4.5 / 300 Hours	AATCC 16.3-2014, Opt. 3
Crocking Resistance	Dry: 5.0 / Wet: 5.0	AATCC 8-2013
Flex Resistance	25,000+	ASTM D2907-03(2010)
Sulfide Stain Resistance	Yes	
Seam Strength: Tack Tear	Warp: 67 / Fill: 64	ASTM D751-06(2011)
Tear Strength: Tongue Tear	Warp: 7.1 / Fill: 6.3	ASTM D751-06(2011)
Stretch and Set	Warp: Stretch 4.17% / Set 2.08% Fill: Stretch 25.00% / Set 4.51% Bias: Stretch 42.36% / Set 4.51%	SAE J855-2009

*ACT® Registered Certification Marks

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass
FMVSS 302	Pass

GENERAL PRODUCT INFORMATION

Country of Origin	Taiwan
HTS Code	5903.10.2090
Roll Size	30 Yards/Roll

Glaze

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65
No added flame retardant chemicals – AB2998 compliant
No added anti-bacterial / anti-microbial chemicals
Phthalate free / PFAS-free
Lead / heavy metal free
BPA free / tris free / formaldehyde free
Does not contain conflict minerals