

Bedford

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	15/16 oz/Linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input checked="" type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED
	<input type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD
	<input type="checkbox"/> PILE
YARN PER INCH	50.6 EPI, 60.7 PPI
YARN SIZE	630D Warp, 630D Fill
MINIMUM YARDAGE CUSTOM COLOR	500 yards
STAIN RESISTANT	Yes
BACKING	SBR
CLEANING CODE	S, Spot clean using a water-free solvent or dry cleaning product. Cleaning by a professional service is recommended. SW, Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

PERFORMANCE

COMPLIES WITH	Resilience TX
---------------	---------------

PHYSICAL PROPERTIES

ABRASION RESISTANCE	100,000+Double Rubs, Method ASTM D 4157-10
BREAKING STRENGTH	280 Warp, 318 Fill, Method ASTM 5034
BRUSH PILL	Class 4.5 , ASTM D3511
SEAM SLIPPAGE	55.0 Warp, 39.8 Fill, Method ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	59.8 Warp, 62.9 Fill, ASTM D2261-13
CROCKING	5 Dry, 5 Wet, AATCC 8
COLORFASTNESS TO LIGHT	Class 4.5, 40 Hours, AATCC16 Option 3

FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
NFPA 260	Pass
UFAC Class I	Pass

TARIFF CODE	5407.52.2060
-------------	--------------