

Clutch

DESCRIPTION

WEIGHT (LINEAR YARD)	30 oz
WIDTH	54"
THICKNESS	1.20 mm
GAUGE	0.052
EMBOSS	SE-757
SURFACE COMPOSITION	100% PVC (Phthalate Free)
SUBSTRATE COMPOSITION	100% Polyester Brushed Knit

GENERAL TREATMENTS

COLORFASTNESS TO LIGHT	200 Hours, CFFA-2 / AATCC 16-Option 3
COLD CRACK	-20 °F, CFFA-6 Federal Standard No. 191A-Method 5874
STAIN RESISTANT	Yes, with Resilience™
BLEACH RESISTANT	Yes, 20% Dilution

PHYSICAL STRENGTH PROPERTIES

ABRASION	200,000 Double Rubs, CFFA-1A / Method ASTM D 4157-92)
COATING ADHESION	11.3 Warp, 8.7 Fill, CFFA 3 / ASTM D751-06
TEAR STRENGTH: TONGUE TEAR	8.4 Warp, 5.6 Fill, CFFA-16b / ASTM D2261-96
BREAKING STRENGTH	74 Warp, 60 Fill, CFFA-17 / ASTM D751-06
SEAM STRENGTH: TACK TEAR	72.5 Warp, 56.6 Fill, CFFA-14 / Method ASTM D751-06
CROCKING	5 Dry, 5 Wet, AATCC-Method 8-2001

FLAME TREATMENTS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS 1	Pass
FMVSS 302	Pass
NFPA 260	Pass
IMO 2010 FTP CODE, PART 8	Pass
ASTM E-84 (ADHERED & UNADHERED): CLASS 1 OR A	Pass

REDUCED ENVIRONMENT IMPACT

- 21P PHTHALATE FREE (INCLUDES ALL PHTHALATES LISTED IN CAL PROP 65 & CPSIA)
- LEAD FREE
- BPA FREE/TRIS FREE/FORMALDEHYDE FREE NFPA 260PASS
- DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks