

Connect

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	30.0 oz
WIDTH	54"
THICKNESS	1.00 mm
SURFACE COMPOSITION	100% PVC
SUBSTRATE COMPOSITION	100% Polyester
SUBSTRATE WEIGHT	4.4 oz

GENERAL TREATMENTS

COLORFASTNESS TO LIGHT	200 Hours, AATCC Test Method 16- 2004, Option 3
COLD CRACK	-20 °F, CFFA-6 Federal Standard No. 191A-Method 5874
STAIN RESISTANCE	Yes
BLEACH RESISTANT	Yes, 10% Dilution

PHYSICAL PROPERTIES

ABRASION	100,000 Double Rubs, CFFA-1A/Method ASTM D 4157-10 ACT STANDARD COTTONDUCK
TEAR STRENGTH	6.8 Warp, 8 Fill, CFFA-16 / ASTM D2261-07a
BREAKING STRENGTH	101 Warp, 93 Fill, CFFA-17 / ASTM D751-06
SEAM STRENGTH TACK TEAR	50 Warp, 50 Fill, CFFA-14 / ASTM D751-06
CROCKING	5 Wet, 5.0 Dry, AATCC-Method 8-2007
COATING ADHESION	10.27 Warp, 11.5 Fil, ASTM D751-06

FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

REDUCED ENVIRONMENTAL IMPACT

- PHthalate FREE (INCLUDES ALL PHthalATES LISTED IN CAL PROP 65 & CPSIA)
- LEAD FREE
- BPA FREE/TRIS FREE/FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks