

## Foundation

### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	30.0oz
WIDTH	54"
THICKNESS	1.00 mm
SURFACE COMPOSITION	100% PVC (Phthalate Free)
SUBSTRATE COMPOSITION	100% Polyester Brushed Knit
SUBSTRATE WEIGHT	4.4 oz

### GENERAL TREATMENTS

COLORFASTNESS TO LIGHT	300 Hours, AATCC Test Method 16-2004, Option 3
COLD CRACK	-20 ° F, CFFA-6 Federal Standard No. 191A-Method 5874
STAIN RESISTANT	Yes
BLEACH RESISTANT	Yes, 10% Dilution

### PHYSICAL STRENGTH PROPERTIES

ABRASION	100,000 DR, CFFA-1A / Method ASTM D 4157-10 Act Standard Cottonduck
TEAR STRENGTH	6.8 Warp, 8 Fill, CFFA-16b / ASTM D2261-07a
BREAKING STRENGTH	101 Warp, 93 Fill, CFFA-17 / ASTM D751-06
SEAM STRENGTH TACK TEAR	50 Warp, 50 Fill, CFFA-14 / ASTM D751-06
CROCKING	5.0 Wet, 5.0 Dry, AATCC-METHOD 8-2007
COATING ADHESION	10.27 Warp, 11.5 Fill, ASTM D751-06

### FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
FMVSS 302	Pass
NFPA 260	Pass

### REDUCED ENVIRONMENTAL IMPACT

- 7P PHTHALATE FREE (INCLUDES ALL PHTHALATES LISTED IN CAL PROP 65 & CPSIA)
- LEAD FREE
- BPA FREE/TRIS FREE/FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS
- DOES NOT CONTAIN ADDED FLAME RETARDANT CHEMICALS



\*ACT® Registered Certification Marks