

Fulton

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD) 17/18 oz/Linear Yard
 WIDTH 54"

PIECE DYED YARN DYED FIBER DYED
 DOBBY JACQUARD PILE

YARN PER INCH 47.5 EPI, 35.6 PPI
 YARN SIZE T150D+T1600D Warp, T8S+T1600D Fill
 MINIMUM YARDAGE CUSTOM COLOR 500 Yards
 COMPOSITION 100% Polyester
 STAIN RESISTANT Yes
 BACKING SBR
 CLEANING CODE S, Spot clean using a water-free solvent or dry cleaning product. Cleaning by a professional service is recommended.
 SW, Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

Performance
 COMPLIES WITH Resilience TX

PHYSICAL PROPERTIES

ABRASION RESISTANCE 100,000+ Double Rubs, CFFA-1A/Method ASTM D 4157-10
 BREAKING STRENGTH 323 Warp, 299 Fill, CFFA/Method ASTM 5034
 BRUSH PILL Class 3.5, CFFA-16b/ASTM D3511
 SEAM SLIPPAGE 39.7 Warp, 33.7 Fill, CFFA-14/Method ASTM D4034-92
 TEAR STRENGTH: TONGUE TEAR 73 Warp, 63 Fill, ASTM D2261-13
 CROCKING 4.5 Dry, 4.5 Wet, AATCC 8
 COLORFASTNESS TO LIGHT Class 5.0, 40 Hours, CFFA-2/AATCC16 Option 3

FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
 NFPA 260 Pass
 UFAC Class I Pass

TARIFF CODE 5407.52.2060