

## Glaze

### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	36.0 oz
WIDTH	54"
THICKNESS	1.10 mm
EMBOSS	SE-890
SURFACE COMPOSITION	100 % PVC (Phthalate Free)
SUBSTRATE COMPOSITION	75% Polyester/25% Cotton

### GENERAL TREATMENTS

COLORFASTNESS TO LIGHT	300 Hours, AATCC Test Method 16-2004, Option 3
COLD CRACK	-20° F, CFFA-6 Federal Standard, No. 191A-Method 5874

### PHYSICAL STRENGTH PROPERTIES

ABRASION	100,000 Double Rubs, CFFA-1A Method ASTM D 4157-10 ACT STANDARD COTTONDUCK
BREAKING STRENGTH	67 Warp, 78 Fill, CFFA-17 / ASTM D751-06 (2011)
SEAM STRENGTH: TACK TEAR	67 Warp, 64 Fill, CFFA-14 / ASTM D751-06 (2011)
TEAR STRENGTH: TONGUE TEAR	7.1 Warp, 6.3 Fill, CFFA-16b / ASTM D751-06(2011)
CROCKING	5 Wet, 5 Dry, CFFA-7/ AATCC 8-2007
STRETCH AND SET	97.9 Warp, 95.5 Fill, CFFA-15/SAE J855 2009

### FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
MVSS 302	Pass
IMO 2010 FTP CODE, PART 8	Pass
NFPA 260	Pass
ASTM E-84 (ADHERED): Class 1 or A	Pass

### REDUCED ENVIRONMENTAL IMPACT

- 21PHTHALATE FREE (INCLUDES ALL PHTHALATES LISTED IN CAL PROP 65 & CPSIA)
- LEAD FREE
- BPA FREE/TRIS FREE/FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks