

Ludlow

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD) 21-22oz/Linear Yard
 WIDTH 54"

PIECE DYED YARN DYED FIBER DYED
 DOBBY JACQUARD PILE

YARN PER INCH 50.0 EPI, 58.9 PPI
 YARN SIZE T1000D Warp, T1000D Fill
 MINIMUM YARDAGE CUSTOM COLOR 500 Yards
 COMPOSITION 100% Polyester
 STAIN RESISTANT Yes
 BACKING SBR
 CLEANING CODE S, Spot clean using a water-free solvent or dry cleaning product. Cleaning by a professional service is recommended.
 SW, Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

PERFORMANCE

COMPLIES WITH Resilience TX™

PHYSICAL PROPERTIES

ABRASION RESISTANCE 100,000+ Double Rubs, CFFA-1A/Method ASTM D 4157-10
 BREAKING STRENGTH 536 Warp, 384 Fill, CFFA/Method ASTM D751-06
 BRUSH PILL Class 4.5, CFFA-16b/ASTM D3511
 SEAM SLIPPAGE 33.6 Warp, 26.7 Fill, CFFA-14/Method ASTM D4034-92
 TEAR STRENGTH 113.8 Warp, 109.0 Fill, ASTM D2261-13
 COLORFASTNESS TO CROCKING 4.5 Dry, 4.5 Wet, AATCC 8
 COLORFASTNESS TO LIGHT Class 4.0, 40 Hours, CFFA-2/AATCC16 Option 3

FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
 NFPA 260 Pass
 UFAC Class I Pass

TARIFF CODE 5407.53.2000

