

Stanton

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	11/12 oz	
WIDTH	54"	
COMPOSITION	100% Polyester	
<input type="checkbox"/> PIECE DYED	<input checked="" type="checkbox"/> YARN DYED	<input type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD	<input type="checkbox"/> PILE
YARN PER INCH	18 EPI, 10 PPI	
YARN SIZE	T9S Warp, T5.5S Fill	
MINIMUM YARDAGE CUSTOM COLOR	500 yards	
STAIN RESISTANT	Yes	
BACKING	SBR	
CONTENT	100% Polyester	
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.	

PERFORMANCE

COMPLIES WITH	Resilience TX™
---------------	----------------

PHYSICAL PROPERTIES

ABRASION	100,000+ Double Rubs, METHOD ASTM D 4157-13
BREAKING STRENGTH AND ELONGATION	302 Warp, 60 Fill, METHOD ASTM 5034
BRUSH PILL	Class 4.5, ASTM D3511
SEAM SPILLAGE	112 Warp, 57.5 Fill, METHOD ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	25.5 Warp, 8.6 Fill, ASTM D2261-13
CROCKING	5 Dry, 5.0 Wet, AATCC-8
COLORFASTNESS TO LIGHT	Class 4.5, 40 Hours, AATCC16 Option 3

FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
NFPA 260	Pass
UFAC CLASS I	Pass

TARIFF CODE	5407.53.2000
-------------	--------------



*ACT® Registered Certification Marks