

## Varick

### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD) 15/16 oz/ Linear Yard  
 WIDTH 54"

- PIECE DYED     YARN DYED     FIBER DYED  
 DOBBY     JACQUARD     PILE

YARN PER INCH 30.5 EPI, 20.32 PPI  
 YARN SIZE 7.7S Warp, T6S Fill  
 MINIMUM YARDAGE CUSTOM COLOR 500 Yards  
 COMPOSITION 85% Polyester/15% Linen  
 STAIN RESISTANT Yes  
 BACKING SPR  
 CLEANING CODE S, Spot clean using a water-free solvent or dry cleaning product. Cleaning by a professional service is recommended. SW, Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

### PERFORMANCE

COMPLIES WITH Resilience TX™

### PHYSICAL PROPERTIES

ABRASION RESISTANCE 100,000+ Double Rubs, Method ASTM D 4157-10  
 BREAKING STRENGTH 245 Warp, 55 Fill, Method ASTM 5034  
 BRUSH PILL Class 5.0, ASTM D3511  
 SEAM SLIPPAGE 56.5 Warp, 69.7 Fill, Method ASTM D4034-92  
 TEAR STRENGTH: TONGUE TEAR 23.2 Warp, 11.0 Fill, ASTM D2261-13  
 CROCKING 4.5 Dry, 4.5 Wet, AATCC 8  
 COLORFASTNESS TO LIGHT Class 4.5, 40 Hours, AATCC16 Option 3

### FLAME RETARDANCY

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass  
 NFPA 260 Pass  
 UFAC CLASS I Pass



\*ACT® Registered Certification Marks