

Pattern: Twist

3/1/2017

The Symphony Collection

General Specifications

Weight (linear yard)	30.0 oz
Width	54 "
Thickness	1.20 mm
Gauge	0.048
Surface Composition	100% PVC
Substrate Composition	100% Brushed Polyester Knit
Substrate Weight	4.4 oz

General Treatments

Colorfastness to Light	300 Hours	ASTM G154-06 & AATCC Test Method 16-2004, Option 3
Cold Crack	-20° F	CFFA-6 Federal Standard No. 191A-Method 5874
Stain Resistant	Yes	with Resilience ^{SR}
Bleach Resistant	Yes	10% Dilution

Physical Strength Properties

Abrasion	250,000 Double Rubs	CFFA-1A / Method ASTM D 4157-10 ACT STANDARD COTTONDUCK
Tear Strength: Tongue Tear	6.9 Warp 10.6 Fill	CFFA-16 / ASTM D2261-07a
Breaking Strength	98 Warp 81 Fill	CFFA-17 / ASTM D751-06
Seam Strength: Tack Tear	58.5 Warp 46.2 Fill	CFFA-14 / Method ASTM D751-06
Crocking	5.0 Dry 5.0 Wet	AATCC-Method 8-2007
Coating Adhesion	8.2 Warp 6.6 Fill	ASTM D751-06

Flame Retardancy Standards

California Technical Bulletin 117:13	Pass
UFAC Class I	Pass
MVSS 302	Pass
NFPA 260	Pass

Reduced Environmental Impact

Phthalate Free (includes all Phthalates listed in CAL Prop 65 & CPSIA)
 Lead Free
 BPA Free/TRIS Free/Formaldehyde Free
 Does not contain Conflict Minerals

TARIFF CODE: 5903.10.2090