

Wilde

GENERAL SPECIFICATIONS

Overall Composition	67% Polyurethane / 28% Polyester / 5% Viscose
Surface Composition	100% Polyurethane (Polycarbonate)
Backing Composition	85% Polyester / 15% Viscose
Weight	20.0 oz. Per Linear Yard
	442.1 gsm
Width	54"
Thickness	1.00 mm
Direction	Non-Directional

PERFORMANCE SPECIFICATIONS

Abrasion Resistance	165,000+ Double Rubs*	ASTM D4157-13
Stain Resistance	Yes, PFAS-free	
Hydrolysis Resistance	7 Weeks	ISO 1419:1995 (Jungle Test)
Anti-Bacterial	Pass	AATCC 147-2011
Bleach Resistance	Yes, 10% Dilution	
Blocking	Rating 1	CFFA-4(2010)
Breaking Strength	Warp: 128 / Fill: 106	ASTM D751-06(2011)
Coating Adhesion	Warp: 4.8 / Fill: 4.3	ASTM D751-06(2011)
Cold Crack	-20° F	CFFA-6a-2010
Colorfastness to Light	Class 5.0 / 200 Hours	AATCC 16.3-2014, Opt. 3
Crocking Resistance	Dry: 5.0 / Wet: 5.0	AATCC 8-2016
Denim Dye Transfer Resistance	Yes	Ford BN 112-09
Flex Resistance	25,000+	ASTM D2097-03(2010)
Ink Resistance	Yes	
Mildew Resistance	Pass	ASTM G21-13
Sulfide Stain Resistance	Yes	
Seam Strength: Tack Tear	Warp: 88.7 / Fill: 87.9	ASTM D751-06(2011)
Tear Strength: Tongue Tear	Warp: 11.3 / Fill: 7.6	ASTM D751-06(2011)
Stretch and Set	Warp: Stretch 0.00% / Set 0.00%	SAE J855-2009
	Fill: Stretch 7.50% / Set 0.00%	
	Bias: Stretch 22.33% / Set 1.73%	



*ACT® Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass

Wilde

GENERAL PRODUCT INFORMATION

Country of Origin	Vietnam
HTS Code	5903.20.2500
Roll Size	30 Yards/Roll

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals

