

## Morton

**GENERAL SPECIFICATIONS** 

WEIGHT (LINEAR YARD) 11/12 oz per linear yard

WIDTH 54"

COMPOSITION 100% Polyester

□ PIECE DYED ■ YARN DYED □ FIBER DYED

■ DOBBY □ JACQUARD □ PILE

YARN PER INCH 62 EPI, 12 PPI

YARN SIZE T150D Warp, T5.5S+T3.7S Fill

BACKING SBR STAIN RESISTANCE C6

CLEANING CODE SW, Spot clean with upholstery shampoo, foam from a mild detergent,

or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not

be removed and dry cleaned.

## PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 100,000+ Double Rubs\* ASTM D4157-13
BREAKING STRENGTH 277 Warp, 239 Fill ASTM D5034-09
BRUSH PILL Class 4.5 ASTM D3511
CROCKING RESISTANCE 4.5 Dry, 5 Wet AATCC 8-2013

COLORFASTNESS TO LIGHT Class 5 AATCC 16.3-2014, Option 3

SEAM SLIPPAGE 107.8 Warp, 96.2 Fill ASTM D4034-92 TEAR STRENGTH: TONGUE TEAR 45.1 Warp, 84.6 Fill ASTM D2261-13

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
UFAC CLASS I Pass
NFPA 260 Pass

## REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS









\*ACT® Registered Certification Marks