

## Traveler

### GENERAL SPECIFICATIONS

#### CONTENT

Surface: 100% PVC (Phthalate Free)  
 Backing: 100% Polyester Brushed Knit

#### WIDTH

54"

#### THICKNESS

1.20 mm

#### GAUGE

0.048

#### WEIGHT

30 oz.

#### ROLL SIZE

30 yards

#### STAIN RESISTANCE

Resilience™

### PERFORMANCE

#### COMPLIES WITH

Resilience™

### PHYSICAL PROPERTIES

#### ABRASION RESISTANCE

250,000+ Double Rubs, ASTM D4157-13 ACT STANDARD COTTONDUCK

#### TEAR STRENGTH: TONGUE TEAR

7.1 Warp, 10.4 Fill, ASTM D2261-13

#### BREAKING STRENGTH

105 Warp, 92 Fill, ASTM D751-06

#### SEAM STRENGTH: TACK TEAR

54.3 Warp, 43 Fill, ASTM D751-06

#### CROCKING

5.0 Wet, 5.0 Dry, AATCC 8-2016

#### FLEX TESTING OF FINISH

25,000 Cycles, ASTM D2097-03(2010)

#### COATING ADHESION

6.3 Warp, 6.3 Fill, ASTM D751-06

#### COLORFASTNESS TO LIGHT

200 Hours, AATCC 16.3-2014 Option 3

#### COLD CRACK

-20°F, CFFA 6a-2010

#### BLEACH RESISTANCE

10% Dilution, AATCC 107-2013

#### SULFIDE STAIN RESISTANCE

Yes

#### STRETCH & SET

	Stretch	Set
Warp	20.0%	2%
Fill	64.4%	4.9%
Bias	24.9%	2.4%

SAE J855 2009

### FLAME TREATMENTS

#### CALIFORNIA FIRE CODE TECHNICAL BULLETIN NO. 117-2013

Pass

#### NFPA 260

Pass

#### UFAC CLASS 1

Pass

#### FMVSS 302

Pass

### REDUCED ENVIRONMENTAL IMPACT

#### PHthalate FREE

#### LEAD FREE

#### BPA FREE/TRIS FREE/FORMALDEHYDE FREE

#### WATER & ENERGY EFFICIENT PRODUCTION



\*ACT® Registered Certification Marks