

This spec has been updated to reflect the removal of flame retardant additives.

## Glaze

### GENERAL SPECIFICATIONS

|                              |                           |
|------------------------------|---------------------------|
| <b>SURFACE COMPOSITION</b>   | 100% PVC (Phthalate Free) |
| <b>SUBSTRATE COMPOSITION</b> | 75% Polyester/25% Cotton  |
| <b>WEIGHT</b>                | 36.0 oz per linear yard   |
| <b>WIDTH</b>                 | 54"                       |
| <b>THICKNESS</b>             | 1.10 mm                   |

### ADDED PERFORMANCE SPECIFICATIONS

|                                 |                   |                           |
|---------------------------------|-------------------|---------------------------|
| <b>STAIN RESISTANCE</b>         | Yes               |                           |
| <b>COLORFASTNESS TO LIGHT</b>   | 300 Hours         | AATCC 16.3-2014, Option 3 |
| <b>BLEACH RESISTANCE</b>        | Yes, 10% Dilution | AATCC 107-13, Modified    |
| <b>COLD CRACK</b>               | -20° F            | CFFA-6a-2007              |
| <b>SULFIDE STAIN RESISTANCE</b> | Yes               |                           |

### PHYSICAL PERFORMANCE SPECIFICATIONS

|                                   |                     |               |
|-----------------------------------|---------------------|---------------|
| <b>ABRASION RESISTANCE</b>        | 100,000 Double Rubs | ASTM D4157-13 |
| <b>BREAKING STRENGTH</b>          | 67 Warp, 78 Fill    | ASTM D751-06  |
| <b>COATING ADHESION</b>           | 11.0 Warp, 9.7 Fill | ASTM D751-06  |
| <b>CROCKING RESISTANCE</b>        | 5 Dry, 5 Wet        | AATCC 8-2013  |
| <b>FLEX RESISTANCE</b>            | 25,000+             | ASTM D2097-03 |
| <b>TEAR STRENGTH: TONGUE TEAR</b> | 7.1 Warp, 6.3 Fill  | ASTM D751-06  |
| <b>SEAM STRENGTH: TACK TEAR</b>   | 67 Warp, 64 Fill    | ASTM D751-06  |

### FLAME RETARDANCY SPECIFICATIONS

|                                      |      |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I                         | Pass |
| NFPA 260                             | Pass |
| FMVSS 302                            | Pass |

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS  
 PHTHALATE FREE  
 LEAD / HEAVY METAL FREE  
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
 DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks