

Lafayette

GENERAL SPECIFICATIONS

<p>WEIGHT (LINEAR YARD)</p> <p>WIDTH</p> <p>COMPOSITION</p> <p><input checked="" type="checkbox"/> PIECE DYED</p> <p><input type="checkbox"/> DOBBY</p> <p>YARN PER INCH</p> <p>YARN SIZE</p> <p>CLEANING CODE</p>	<p><input type="checkbox"/> YARN DYED</p> <p><input type="checkbox"/> JACQUARD</p> <p>20.0/21.0 oz per linear yard</p> <p>54"</p> <p>100% Polyester</p> <p><input type="checkbox"/> FIBER DYED</p> <p><input checked="" type="checkbox"/> PILE</p> <p>61.0 EPI, 64.0 PPI</p> <p>300D Warp, 36/2 NM Fill</p> <p>S, Spot clean using water-free solvent or dry cleaning product. Cleaning by a professional service is recommended.</p>
--	---

PHYSICAL PERFORMANCE SPECIFICATIONS

<p>ABRASION RESISTANCE</p> <p>BREAKING STRENGTH</p> <p>BRUSH PILL</p> <p>CROCKING RESISTANCE</p> <p>COLORFASTNESS TO LIGHT</p> <p>SEAM SLIPPAGE</p> <p>TEAR STRENGTH: TONGUE TEAR</p>	<p>100,000+ Double Rubs</p> <p>258 Warp, 231 Fill</p> <p>Class 5.0</p> <p>4.5 Dry, 4.5 Wet</p> <p>Class 4.5</p> <p>114.1 Warp, 117.7 Fill</p> <p>16.6 Warp, 24.8 Fill</p>	<p>ASTM D4157-10</p> <p>ASTM D5034-09</p> <p>ASTM D3511</p> <p>AATCC 8-2007</p> <p>AATCC 16.3-2012, Option 3</p> <p>ASTM D4034-92</p> <p>ASTM D2261-13</p>
---	---	--

FLAME RETARDANCY SPECIFICATIONS

<p>CALIFORNIA TECHNICAL BULLETIN 117:13</p> <p>UFAC CLASS I</p> <p>NFPA 260</p>	<p>Pass</p> <p>Pass</p> <p>Pass</p>
---	-------------------------------------

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT

NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS

LEAD / HEAVY METAL FREE

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks