

This is an up-to-date spec sheet. This pattern never contained flame retardant or anti-bacterial additives.

Primary

GENERAL SPECIFICATIONS

| | |
|------------------------------|-------------------------|
| SURFACE COMPOSITION | 100% PVC |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 24.0 oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 0.80 mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|---------------------------------|-------------------|------------------------|
| STAIN RESISTANCE | Yes | |
| COLORFASTNESS TO LIGHT | 200 Hours | ASTM G26-96, Method C |
| MILDEW RESISTANCE | Pass | ASTM G21-13 |
| BLEACH RESISTANCE | Yes, 10% Dilution | AATCC 107-13, Modified |
| COLD CRACK | -10° F | CFFA-6a-2007 |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|----------------------------|----------------------|---------------|
| ABRASION RESISTANCE | 30,000+ Double Rubs | ASTM D4157-92 |
| BREAKING STRENGTH | 75.8 Warp, 64.9 Fill | ASTM D751-06 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |

REDUCED ENVIRONMENTAL IMPACT

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS

