

This spec sheet has been updated to reflect the removal of flame retardants.

## Bronte

### GENERAL SPECIFICATIONS

<b>SURFACE COMPOSITION</b>	100% PVC
<b>SUBSTRATE COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	32.0 oz per linear yard
<b>WIDTH</b>	54"
<b>THICKNESS</b>	1.02 mm

### ADDED PERFORMANCE SPECIFICATIONS

<b>STAIN RESISTANCE</b>	Yes	
<b>UV RESISTANCE</b>	1,000 Hours	ASTM G26-96 Method C
<b>BLEACH RESISTANCE</b>	Yes, 20% Dilution	AATCC 107-13, Modified
<b>MILDEW RESISTANCE</b>	Pass	ASTM G21-13
<b>COLD CRACK</b>	-20° F	CFFA-6a-2007
<b>SULFIDE STAIN RESISTANCE</b>	Yes	

### PHYSICAL PERFORMANCE SPECIFICATIONS

<b>ABRASION RESISTANCE</b>	500,000+ Double Rubs	ASTM D4157-07
<b>BREAKING STRENGTH</b>	89.2 Warp, 103 Fill	ASTM D751-06
<b>FLEX RESISTANCE</b>	25,000+	ASTM D2097-03
<b>TEAR STRENGTH: TONGUE TEAR</b>	25.8 Warp, 28 Fill	ASTM D751-06

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
 NO ADDED ANTI-BACTERIAL CHEMICALS  
 LEAD / HEAVY METAL FREE  
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
 DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks