

Champlain

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	21.5 oz per linear yard
WIDTH	54"
COMPOSITION	94% Polyester/4% Polyurethane/2% Silicone
<input checked="" type="checkbox"/> PIECE DYED <input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> YARN DYED <input type="checkbox"/> JACQUARD
	<input type="checkbox"/> FIBER DYED <input type="checkbox"/> PILE
YARN PER INCH	243.84 EPI, 228.6 PPI
YARN SIZE	900D+300D Warp, 300D+900D Fill
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC, Lightly spray with a 10% dilution of Household Bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs	ASTM D4157-13
HYDROSTATIC PRESSURE (SUTER)	270+cm (maximum)	AATCC 127-2013, Option 1
BREAKING STRENGTH	302 Warp, 329 Fill	ASTM D5034-09
BRUSH PILL	Class 5	ASTM D3511
CROCKING RESISTANCE	4.5 Dry, 4.5 Wet	AATCC 8-2016
COLORFASTNESS TO LIGHT	Class 4.5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	82.5 Warp, 80 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	69.5 Warp, 93.7 Fill	ASTM D2261-13

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.

