

This spec sheet has been updated to reflect the removal of flame retardant and anti-bacterial additives.

Seaquest

GENERAL SPECIFICATIONS

SURFACE COMPOSITION	100% PVC
SUBSTRATE COMPOSITION	100% Polyester
WEIGHT	32.0 oz per linear yard
WIDTH	54"
THICKNESS	1.02 mm

ADDED PERFORMANCE SPECIFICATIONS

STAIN RESISTANCE	Yes	
COLORFASTNESS TO LIGHT	1,000 Hours	AATCC 16.3-2014, Option 3
COLORFASTNESS TO UV	1,000 Hours	ASTM G154-12a
MILDEW RESISTANCE	Pass	ASTM G21-00
BLEACH RESISTANCE	Yes, 20% Dilution	AATCC 107-13, Modified
COLD CRACK	-20° F	FFFA-6a-2007
PINK STAIN RESISTANCE	Pass	ASTM E1428
SULFIDE STAIN RESISTANCE	Yes	

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	175,000 Double Rubs	ASTM D4157-13
BREAKING STRENGTH	89.2 Warp, 102.7 Fill	ASTM D751-06
FLEX RESISTANCE	25,000+	ASTM D2097-03

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

REDUCED ENVIRONMENTAL IMPACT

- THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
- NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
- NO ADDED ANTI-BACTERIAL CHEMICALS
- 7P PHTHALATE FREE
- LEAD / HEAVY METAL FREE
- BPA FREE / TRIS FREE / FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks