

Bronte

GENERAL SPECIFICATIONS

| | |
|------------------------------|-----------------------|
| SURFACE COMPOSITION | 100% PVC |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 32.oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 1.00 mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|---------------------------------|-------------------|----------------------|
| STAIN RESISTANCE | Yes | |
| UV RESISTANCE | 1,000 Hours | ASTM G26-96 Method C |
| BLEACH RESISTANCE | Yes, 10% Dilution | |
| MILDEW RESISTANCE | Pass | ASTM G21-13 |
| COLD CRACK | -20° F | CFFA-6a-2007 |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|-----------------------|---------------|
| ABRASION RESISTANCE | 500,000+ Double Rubs* | ASTM D4157-07 |
| BREAKING STRENGTH | 89.2 Warp, 103 Fill | ASTM D751-06 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |
| TEAR STRENGTH: TONGUE TEAR | 25.8 Warp, 28 Fill | ASTM D751-06 |

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |
| FMVSS 302 | Pass |

REDUCED ENVIRONMENTAL IMPACT

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks