

Essex

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	16/17 oz per linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input type="checkbox"/> PIECE DYED	<input type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> PILE
<input checked="" type="checkbox"/> YARN DYED	
<input type="checkbox"/> JACQUARD	
YARN PER INCH	34.3 EPI, 31.8 PPI
YARN SIZE	1010D Warp, 1010D Fill
BACKING	SBR
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	288 Warp, 195 Fill	ASTM D5034-09
BRUSH PILL	Class 5	ASTM D3511
CROCKING RESISTANCE	5 Dry, 5 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 4	AATCC 16.3-2012, Option 3
SEAM SLIPPAGE	108.8 Warp, 118.0 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	33.6 Warp, 25.1 Fill	ASTM D2261-13

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks