

Fulton

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD) WIDTH COMPOSITION <input type="checkbox"/> PIECE DYED <input checked="" type="checkbox"/> DOBBY	<input checked="" type="checkbox"/> YARN DYED <input type="checkbox"/> JACQUARD	17/18 oz per linear yard 54" 100% Polyester <input type="checkbox"/> FIBER DYED <input type="checkbox"/> PILE
YARN PER INCH YARN SIZE BACKING CLEANING CODE	47.5 EPI, 36.6 PPI T150D+T1600D Warp, T8S+T1600D Fill SBR SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.	

t

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE BREAKING STRENGTH BRUSH PILL CROCKING RESISTANCE COLORFASTNESS TO LIGHT SEAM SLIPPAGE TEAR STRENGTH: TONGUE TEAR	100,000+ Double Rubs* 323 Warp, 299 Fill Class 3.5 4.5 Dry, 4.5 Wet Class 5 39.7 Warp, 33.7 Fill 73 Warp, 63 Fill	ASTM D4157-13 ASTM D5034-09 ASTM D3511 AATCC 8-2013 AATCC 16.3-2014, Option 3 ASTM D4034-92 ASTM D2261-13
--	---	---

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 UFAC CLASS I NFPA 260	Pass Pass Pass
--	----------------------

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks