

Harrison Wool

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	15/16 oz per linear yard	
WIDTH	54"	
COMPOSITION	70% Wool / 20% Polyester / 5% Acrylic / 5% Nylon	
<input type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED	<input checked="" type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD	<input type="checkbox"/> PILE
YARN PER INCH	38.1 EPI, 34.5 PPI	
YARN SIZE	MN 8.3 Warp, MN 8.3 Fill	
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.	

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	75,000+ Double Rubs*	ASTM D4966-12
BREAKING STRENGTH	108.3 Warp, 57.4 Fill	ASTM D5034-09
BRUSH PILL	Class 3	ASTM D3511
CROCKING RESISTANCE	5 Dry, 5 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	86.9 Warp, 56.0 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	11.8 Warp, 7.0 Fill	ASTM D2261-13

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks