

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

Imperial 70

GENERAL SPECIFICATIONS

| | |
|------------------------------|-------------------------|
| SURFACE COMPOSITION | 70 Denier Nylon |
| SUBSTRATE COMPOSITION | 100% PVC |
| WEIGHT | 19.5 oz per linear yard |
| WIDTH | 58" |
| THICKNESS | 0.35 mm |

ADDED PERFORMANCE SPECIFICATIONS_s

| | | |
|-------------------------------|----------|---------|
| COLORFASTNESS TO LIGHT | 20 Hours | |
| COLD CRACK | -10° F | CFFA-6a |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|----------------------|------------|
| BREAKING STRENGTH | 182 Warp, 151 Fill | ASTM D751 |
| COATING ADHESION | 10.6 Warp, 10.5 Fill | ASTM D751- |
| TEAR STRENGTH: TONGUE TEAR | 3 Warp, 2.1 Fill | ASTM D2261 |
| SEAM STRENGTH: TACK TEAR | 945.5 lbs/inch | ASTM D624 |

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
|--------------------------------------|------|



*ACT® Registered Certification Marks