

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

Notion

GENERAL SPECIFICATIONS

| | |
|------------------------------|---------------------------|
| SURFACE COMPOSITION | 100% PVC (Phthalate Free) |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 31 oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 1.20 mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|--------------------------------------|-------------------|---------------------------|
| STAIN RESISTANCE | Yes | |
| COLORFASTNESS TO LIGHT | 300 Hours | AATCC 16.3-2014, Option 3 |
| BLEACH RESISTANCE | Yes, 10% Dilution | |
| COLD CRACK | -20° F | CFFA-6a-2007 |
| DENIM DYE TRANSFER RESISTANCE | Yes | |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|-----------------------|---------------|
| ABRASION RESISTANCE | 250,000+ Double Rubs* | ASTM D4157-13 |
| BREAKING STRENGTH | 95 Warp, 73 Fill | ASTM D751-06 |
| COATING ADHESION | 8.0 Warp, 8.1 Fill | ASTM D751-06 |
| CROCKING RESISTANCE | 5 Dry, 5 Wet | AATCC 8-2016 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |
| TEAR STRENGTH: TONGUE TEAR | 7.2 Warp, 11.0 Fill | ASTM D751-06 |
| SEAM STRENGTH: TACK TEAR | 48.8 Warp, 40.0 Fill | ASTM D751-06 |

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |
| FMVSS 302 | Pass |

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 PHTHALATE FREE
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks