

Buffalo

GENERAL SPECIFICATIONS

SURFACE COMPOSITION	100% PVC
SUBSTRATE COMPOSITION	100% Polyester
WEIGHT	33.0 oz per linear yard
WIDTH	54"
THICKNESS	1.50 mm

ADDED PERFORMANCE SPECIFICATIONS

COLORFASTNESS TO UV	200 Hours	AATCC 16.3-2014, Option 3
COLD CRACK	-10° F	CFFA-6a-2007

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	30,000+ Double Rubs	ASTM D4157-02
----------------------------	---------------------	---------------

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks