

## Bedford

### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	15/16 oz per linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input checked="" type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD
	<input type="checkbox"/> FIBER DYED
	<input type="checkbox"/> PILE
YARN PER INCH	50.6 EPI, 60.7 PPI
YARN SIZE	630D Warp, 630D Fill
BACKING	SBR
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

### PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	280 Warp, 318 Fill	ASTM D5034-09
BRUSH PILL	Class 4.5	ASTM D3511
CROCKING RESISTANCE	5 Dry, 5 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 4.5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	55.0 Warp, 39.8 Fill	ASTM D434-95, Modified
TEAR STRENGTH: TONGUE TEAR	59.8 Warp, 62.9 Fill	ASTM D2261-13

*\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS  
 LEAD / HEAVY METAL FREE  
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
 DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks