

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

## Connect

### GENERAL SPECIFICATIONS

|                              |                       |
|------------------------------|-----------------------|
| <b>SURFACE COMPOSITION</b>   | 100% PVC              |
| <b>SUBSTRATE COMPOSITION</b> | 100% Polyester        |
| <b>WEIGHT</b>                | 30 oz per linear yard |
| <b>WIDTH</b>                 | 54"                   |
| <b>THICKNESS</b>             | 1.00 mm               |

### ADDED PERFORMANCE SPECIFICATIONS

|                                 |                   |                           |
|---------------------------------|-------------------|---------------------------|
| <b>STAIN RESISTANCE</b>         | Yes               |                           |
| <b>COLORFASTNESS TO LIGHT</b>   | 300 Hours         | AATCC 16.3-2014, Option 3 |
| <b>BLEACH RESISTANCE</b>        | Yes, 10% Dilution |                           |
| <b>COLD CRACK</b>               | -20° F            | CFFA-6a-2010              |
| <b>SULFIDE STAIN RESISTANCE</b> | Yes               |                           |

### PHYSICAL PERFORMANCE SPECIFICATIONS

|                                   |                       |               |
|-----------------------------------|-----------------------|---------------|
| <b>ABRASION RESISTANCE</b>        | 100,000+ Double Rubs* | ASTM D4157-13 |
| <b>BREAKING STRENGTH</b>          | 101 Warp, 93 Fill     | ASTM D751-06  |
| <b>COATING ADHESION</b>           | 10.2 Warp, 11.5 Fill  | ASTM D751-06  |
| <b>CROCKING RESISTANCE</b>        | 5 Dry, 5 Wet          | AATCC 8-2013  |
| <b>FLEX RESISTANCE</b>            | 25,000+               | ASTM D2097-03 |
| <b>TEAR STRENGTH: TONGUE TEAR</b> | 6.8 Warp, 8.0 Fill    | ASTM D751-06  |
| <b>SEAM STRENGTH: TACK TEAR</b>   | 50 Warp, 50 Fill      | ASTM D751-06  |

*\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

### FLAME RETARDANCY SPECIFICATIONS

|                                      |      |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I                         | Pass |
| NFPA 260                             | Pass |
| FMVSS 302                            | Pass |

### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65  
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT  
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS  
 7P PHTHALATE FREE  
 LEAD / HEAVY METAL FREE  
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE  
 DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks