

## Essex

G	FΝ	IFR	ΔΙ	SP	FC.	IFI	ICA <sup>-</sup>	$\Gamma \Gamma C$	NS.
$\mathbf{v}$	-1	4 1 1 1	$\neg$		-			-	$\prime$ I V $\sim$

WEIGHT (LINEAR YARD) 16/17 oz per linear yard

WIDTH 54"

COMPOSITION 100% Polyester

☐ PIECE DYED ☐ FIBER DYED ☐ FIBER DYED

■ DOBBY □ JACQUARD □ PILE

YARN PER INCH 34.3 EPI, 31.8 PPI

YARN SIZE 1010D Warp, 1010D Fill

BACKING SBR STAIN RESISTANCE C6

CLEANING CODE SW, Spot clean with upholstery shampoo, foam from a mild detergent,

or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not

be removed and dry cleaned.

## PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 100,000+ Double Rubs\* ASTM D4157-13
BREAKING STRENGTH 288 Warp, 195 Fill ASTM D5034-09
BRUSH PILL Class 5 ASTM D3511
CROCKING RESISTANCE 5 Dry, 5 Wet AATCC 8-2013

COLORFASTNESS TO LIGHT Class 4 AATCC 16.3-2012, Option 3

SEAM SLIPPAGE108.8 Warp, 118.0 FillASTM D4034-92TEAR STRENGTH: TONGUE TEAR33.6 Warp, 25.1 FillASTM D2261-13

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass
UFAC CLASS I Pass
NFPA 260 Pass

## REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
LEAD / HEAVY METAL FREE
BPA FREE / TRIS FREE / FORMALDEHYDE FREE
DOES NOT CONTAIN CONFLICT MINERALS









\*ACT® Registered Certification Marks