

Gramercy

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	19 oz per linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input checked="" type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED
<input type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD
	<input type="checkbox"/> FIBER DYED
	<input checked="" type="checkbox"/> PILE
YARN PER INCH	76.2 EPI, 48.3 PPI
YARN SIZE	300-450DN Warp, 300-450DN Fill
BACKING	None
STAIN RESISTANCE	C6
CLEANING CODE	S, Spot clean using water-free solvent or dry cleaning product. Cleaning by a professional service is recommended.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	273 Warp, 129 Fill	ASTM D5034-09
BRUSH PILL	Class 5	ASTM D3511
CROCKING RESISTANCE	5 Dry, 4.5 Wet	AATCC 8-2016
COLORFASTNESS TO LIGHT	Class 4	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	78.5 Warp, 73.5 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	25.7 Warp, 30.0 Fill	ASTM D2261-13

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks