

## Leathertex

### GENERAL SPECIFICATIONS

<b>SURFACE COMPOSITION</b>	100% PVC
<b>SUBSTRATE COMPOSITION</b>	100% Polyester
<b>WEIGHT</b>	67.0 oz per linear yard
<b>WIDTH</b>	54"
<b>THICKNESS</b>	3.00 mm

### ADDED PERFORMANCE SPECIFICATIONS

<b>STAIN RESISTANCE</b>	Yes	
<b>COLORFASTNESS TO UV</b>	200 Hours	ASTM G26-96, Method C
<b>MILDEW RESISTANCE</b>	Pass	ASTM G21-96
<b>COLD CRACK</b>	-20° F	CFFA-6a-2007

### PHYSICAL PERFORMANCE SPECIFICATIONS

<b>ABRASION RESISTANCE</b>	50,000 Double Rubs	ASTM D4157-10
----------------------------	--------------------	---------------

### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
BIFMA CS-191-53, SECTION 3	Pass
BIFMA UPHOLSTERY, SECTION 4	Pass
FMVSS 302	Pass



\*ACT® Registered Certification Marks