

This spec has been updated to reflect the removal of flame retardant additives.

San Remo

GENERAL SPECIFICATIONS

SURFACE COMPOSITION	100% PVC (Phthalate Free)
SUBSTRATE COMPOSITION	75% Polyester/25% Cotton
WEIGHT	36 oz per linear yard
WIDTH	54"
THICKNESS	1.10 mm

ADDED PERFORMANCE SPECIFICATIONS

STAIN RESISTANCE	Yes	
COLORFASTNESS TO LIGHT	300 Hours	AATCC 16.3-2014, Option 3
BLEACH RESISTANCE	Yes, 10% Dilution	
COLD CRACK	-20° F	CFFA-6a-2007
SULFIDE STAIN RESISTANCE	Yes	

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-92
BREAKING STRENGTH	68 Warp, 70 Fill	ASTM D751-98
COATING ADHESION	17.8 Warp, 7.8 Fill	ASTM D751-98
CROCKING RESISTANCE	4 Dry, 5 Wet	AATCC 8-07
FLEX RESISTANCE	25,000+	ASTM D2097-03
TEAR STRENGTH: TONGUE TEAR	7.1 Warp, 6.3 Fill	ASTM D751-98
SEAM STRENGTH: TACK TEAR	72 Warp, 72 Fill	ASTM D751-98

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

- THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
- NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
- NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
- PHthalate FREE
- LEAD / HEAVY METAL FREE
- BPA FREE / TRIS FREE / FORMALDEHYDE FREE
- DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks