

This is an up-to-date spec sheet. This pattern never contained flame retardant, anti-bacterial, or anti-microbial additives.

Steinbeck

GENERAL SPECIFICATIONS

| | |
|------------------------------|--|
| SURFACE COMPOSITION | 95% Polyurethane (Polycarbonate) / 5% Silicone |
| SUBSTRATE COMPOSITION | 100% Polyester |
| WEIGHT | 19 oz per linear yard |
| WIDTH | 54" |
| THICKNESS | 1.00 mm |

ADDED PERFORMANCE SPECIFICATIONS

| | | |
|--------------------------------------|-------------------|-----------------------------|
| HYDROLYSIS RESISTANCE | 15 weeks | ISO 1419:1995 (Jungle Test) |
| STAIN RESISTANCE | Yes | |
| COLORFASTNESS TO LIGHT | 200 Hours | AATCC 16.3-2014, Option 3 |
| BLEACH RESISTANCE | Yes, 10% Dilution | |
| MILDEW RESISTANCE | Pass | ASTM G21-13 |
| ANTI-BACTERIAL | Pass | AATC 147-2011 |
| COLD CRACK | -20° F | CFFA-6a-2007 |
| DENIM DYE TRANSFER RESISTANCE | Yes | Ford BN 112-09 |
| SULFIDE STAIN RESISTANCE | Yes | |

PHYSICAL PERFORMANCE SPECIFICATIONS

| | | |
|-----------------------------------|--------------------------------|---------------|
| ABRASION RESISTANCE | 300,000+ Double Rubs* | ASTM D4157-13 |
| BREAKING STRENGTH | 182 Warp, 126 Fill | ASTM D751-06 |
| COATING ADHESION | Full Bond Warp, Full Bond Fill | ASTM D751-06 |
| CROCKING RESISTANCE | 5 Dry, 5 Wet | AATCC 8-2016 |
| FLEX RESISTANCE | 25,000+ | ASTM D2097-03 |
| TEAR STRENGTH: TONGUE TEAR | 11.0 Warp, 15.0 Fill | ASTM D751-06 |
| SEAM STRENGTH: TACK TEAR | 67.08 Warp, 65.3 Fill | ASTM D751-06 |

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

| | |
|--------------------------------------|------|
| CALIFORNIA TECHNICAL BULLETIN 117:13 | Pass |
| UFAC CLASS I | Pass |
| NFPA 260 | Pass |

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.



*ACT® Registered Certification Marks