

Varick

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD) 15/16 oz per linear yard

WIDTH 54"

COMPOSITION 85% Polyester / 15% Linen

■ PIECE DYED ☐ YARN DYED ☐ FIBER DYED

DOBBY ☐ JACQUARD ☐ PILE

YARN PER INCH 30.5 EPI, 20.3 PPI YARN SIZE 7.7S Warp, T6S Fill

BACKING SBR STAIN RESISTANCE C6

CLEANING CODE SW, Spot clean with upholstery shampoo, foam from a mild detergent,

or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not

be removed and dry cleaned.

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE 100.000+ Double Rubs* ASTM D4157-13 **BREAKING STRENGTH** 245 Warp, 55 Fill ASTM D5034-09 **BRUSH PILL** Class 5 **ASTM D3511** CROCKING RESISTANCE **AATCC 8-2013** 4.5 Dry, 4.5 Wet

COLORFASTNESS TO LIGHT Class 4 AATCC 16.3-2014, Option 3

SEAM SLIPPAGE 139.8 Warp, 54.5 Fill ASTM D4034-92 TEAR STRENGTH: TONGUE TEAR 56.5 Warp, 69.7 Fill ASTM D2261-13

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13 Pass UFAC CLASS I Pass **NFPA 260** Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS LEAD / HEAVY METAL FREE BPA FREE / TRIS FREE / FORMALDEHYDE FREE DOES NOT CONTAIN CONFLICT MINERALS







