Constance

GENERAL SPECIFICATIONS WEIGHT (LINEAR YARD) WIDTH COMPOSITION

□ PIFCF DYFD DOBBY

☐ YARN DYFD □ JACQUARD

YARN PER INCH YARN SIZE BACKING MINIMUM YARDAGE CUSTOM COLOR CLEANING CODE

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE HYDROSTATIC PRESSURE (SUTER) BREAKING STRENGTH **BRUSH PILL** CROCKING RESISTANCE COLORFASTNESS TO LIGHT SEAM SLIPPAGE TEAR STRENGTH: TONGUE TEAR **BLEACH RESISTANCE**

100.000+ Double Rubs* 270+cm (maximum) 215 Warp, 170 Fill Class 5 5 Dry, 5 Wet Class 5, 40 hours 87.5 Warp, 93 Fill 27.3 Warp, 24 Fill Yes, 10% Dilution

Pass Pass Pass

15.5 oz per linear yard

■ FIBER DYED

Polvurethane

500 Yards

25.4 EPI, 23.6 PPI

1250D Warp. 1250D Fill

be removed and dry cleaned.

88% Polyester / 10% Polyurethane / 2% Silicone

wipe or rinse with fresh water and blot dry.

SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not

BC, Lightly spray with a 10% dilution of Household Bleach and water. After the appropriate contact time, blot surface dry and

54"

D PILE

ASTM D4157-13 AATCC 127-13, Option 1 ASTM D5034-09 ASTM D3511 AATCC 8-2016 AATCC 16.3-2014 ASTM D4034-92 ASTM D2261-13

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	
UFAC CLASS I	
NFPA 260	

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS LEAD / HEAVY METAL FREE BPA FREE / TRIS FREE / FORMALDEHYDE FREE DOES NOT CONTAIN CONFLICT MINERALS



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer Practice Greenhealth does not verify this information.



*ACT® Registered Certification Marks