

Lugano

GENERAL SPECIFICATIONS

Overall Composition	88% Polyester / 7% Acrylic / 3% Polyurethane / 2% Silicone		
Backing Composition	Polyurethane		
Stain Repellent	Silicone Based, PFAS-free		
Weight	24.9 oz. Per Linear Yard		
	550 gsm		
Width	54"		
Direction	Up the Roll		
Weave Construction	<input type="checkbox"/> Dobby	<input checked="" type="checkbox"/> Jacquard	<input type="checkbox"/> Pile
Dyeing Type	<input type="checkbox"/> Piece Dyed	<input checked="" type="checkbox"/> Yarn Dyed	<input type="checkbox"/> Fiber Dyed
Fiber Composition (Synthetic/Natural)	100% Synthetic Fiber		
Fiber Type (Filament/Spun/Staple)	30% Filament / 70% Staple		
Staple Yarns Combed or Carded	Carded		
High Tenacity Yarn	No		
Textured Yarn	No		
Yarns Per Inch	Warp: 167.6 EPI / Fill: 24.6 PPI		
Yarns Per Centimeter	Warp: 66 / Fill: 9.7		
Yarn Size	Warp: 150D / Fill: 2.6N		
Yarns Twisted 472 Turns+/Meter	No		

PERFORMANCE SPECIFICATIONS

Abrasion Resistance	100,000+ Double Rubs*	ASTM D4157-13(2017)
Stain Resistance	Yes, PFAS-free	
Bleach Resistance	Yes, 10% Dilution	
Breaking Strength	Warp: 308 / Fill: 221	ASTM D5034-21
Brush Pill	Class 4.5	ASTM D3511
Colorfastness to Light	Class 5.0 / 40 Hours	AATCC 16.3, Opt. 3 - 2020
Crocking Resistance	Dry: 4.5 / Wet: 5.0	AATCC 8-2016
Seam Slippage	Warp: 113 / Fill: 124	ASTM D4034
Tear Strength: Tongue Tear	Warp: 28.2 / Fill: 28.5	ASTM D2261-13(2017)
Water Repellency Spray Test	100	AATCC 22-2017
Water Resistance Hydrostatic Pressure	270+ cm (maximum)	AATCC 127-2013, Opt. 1



*ACT® Registered Certification Marks

*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan

FLAMMABILITY SPECIFICATIONS

California TB 117:13	Pass
UFAC Class I	Pass
NFPA 260	Pass

Lugano

GENERAL PRODUCT INFORMATION

Country of Origin	China
HTS Code	5407.52.2060
Roll Size	45 Yards/Roll

CLEANING CODE

Cleaning Code: SW, BC

For complete cleaning information, please refer to the Cleaning and Care Guide.

SPECIAL HANDLING

Some types of adhesive tape may delaminate the backing off of Supreen fabric. It is recommended to use self-clinging stretch wrap instead of tape to secure the roll.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals – AB2998 compliant

No added anti-bacterial / anti-microbial chemicals

PFAS-free

Lead / heavy metal free

BPA free / tris free / formaldehyde free

Does not contain conflict minerals



Disclaimer: This product meets the Healthy Interior goals of the Safer Chemical Challenge according to the manufacturer. Practice Greenhealth does not verify this information.