

### Astor Wool

#### GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	23.5 oz per linear yard	
WIDTH	54"	
COMPOSITION	45% Wool / 30% Cotton / 15% Polyester / 10% Acrylic	
<input type="checkbox"/> PIECE DYED	<input type="checkbox"/> YARN DYED	<input checked="" type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> JACQUARD	<input type="checkbox"/> PILE
YARN PER INCH	30.0 EPI, 36.0 PPI	
YARN SIZE	4/8300 Warp, 3/2800 Fill	
BACKING	None	
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.	

#### PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4966-12E1
BREAKING STRENGTH	170 Warp, 84 Fill	ASTM D5034-09
BRUSH PILL	Class 4	ASTM D3511
CROCKING RESISTANCE	4.5 Dry, 4.5 Wet	AATCC 8-2016
COLORFASTNESS TO LIGHT	Class 5	AATCC 16.3-2014, Option 3
SNAG RESISTANCE	4.0 Warp, 4.5 Fill	ASTM D3939
SEAM SLIPPAGE	93.5 Warp, 45.0 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	32.3 Warp, 22.9 Fill	ASTM D2261-13

\*Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

#### FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

#### REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT

NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS

LEAD / HEAVY METAL FREE

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS



\*ACT® Registered Certification Marks