

Impulse

GENERAL SPECIFICATIONS

SURFACE COMPOSITION	100% PVC (Phthalate Free)
SUBSTRATE COMPOSITION	100% Polyester
WEIGHT	30 oz per linear yard
WIDTH	54"
THICKNESS	0.80 mm
COUNTRY OF ORIGIN	India

ADDED PERFORMANCE SPECIFICATIONS

STAIN RESISTANCE	Yes	
COLORFASTNESS TO LIGHT	200 Hours	AATCC 16.3-2004, Option 3
BLEACH RESISTANCE	Yes, 10% Dilution	
COLD CRACK	-10° F	CFFA-6a-2007

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs	ASTM D4157-10
FLEX RESISTANCE	25,000+	ASTM D2097-03
BREAKING STRENGTH	79.1 Warp, 70.5 Fill	ASTM D751-06
COATING ADHESION	6.90 Warp, 4.97 Fill	ASTM D751-19
CROCKING RESISTANCE	4.5 Dry, 5 Wet	AATCC 8-2007
TEAR STRENGTH: TONGUE TEAR	4.2 Warp, 8.3 Fill	ASTM D2261-07
SEAM STRENGTH: TACK TEAR	46.3 Warp, 32.6 Fill	ASTM D751-06
ELONGATION	37.2% Warp, 120.5% Fill	ASTM D751-06
STRETCH AND SET	Warp 12.85% Stretch, 1.04% Set Fill 72.92% Stretch, 10.94% Set Bias 19.58% Stretch, 1.91% Set	SAE J855-2009

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass
FMVSS 302	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT

NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS

PHthalate FREE

LEAD / HEAVY METAL FREE

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks