

Fulton

GENERAL SPECIFICATIONS

WEIGHT (LINEAR YARD)	17/18 oz per linear yard
WIDTH	54"
COMPOSITION	100% Polyester
<input type="checkbox"/> PIECE DYED	<input type="checkbox"/> FIBER DYED
<input checked="" type="checkbox"/> DOBBY	<input type="checkbox"/> PILE
<input checked="" type="checkbox"/> YARN DYED	
<input type="checkbox"/> JACQUARD	
YARN PER INCH	47.5 EPI, 36.6 PPI
YARN SIZE	T150D+T1600D Warp, T8S+T1600D Fill
BACKING	SBR
STAIN RESISTANCE	PFAS Free
CLEANING CODE	SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.

t

PHYSICAL PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	100,000+ Double Rubs*	ASTM D4157-13
BREAKING STRENGTH	323 Warp, 299 Fill	ASTM D5034-09
BRUSH PILL	Class 3.5	ASTM D3511
CROCKING RESISTANCE	4.5 Dry, 4.5 Wet	AATCC 8-2013
COLORFASTNESS TO LIGHT	Class 5	AATCC 16.3-2014, Option 3
SEAM SLIPPAGE	39.7 Warp, 33.7 Fill	ASTM D4034-92
TEAR STRENGTH: TONGUE TEAR	73 Warp, 63 Fill	ASTM D2261-13

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

CALIFORNIA TECHNICAL BULLETIN 117:13	Pass
UFAC CLASS I	Pass
NFPA 260	Pass

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65
 NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT
 NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS
 LEAD / HEAVY METAL FREE
 BPA FREE / TRIS FREE / FORMALDEHYDE FREE
 DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks