

Walker

GENERAL SPECIFICATIONS

<p>WEIGHT (LINEAR YARD)</p> <p>WIDTH</p> <p>COMPOSITION</p> <p><input checked="" type="checkbox"/> PIECE DYED</p> <p><input checked="" type="checkbox"/> DOBBY</p> <p>YARN PER INCH</p> <p>YARN SIZE</p> <p>BACKING</p> <p>STAIN RESISTANCE</p> <p>CLEANING CODE</p>	<p><input type="checkbox"/> YARN DYED</p> <p><input type="checkbox"/> JACQUARD</p>	<p>13.6 oz per linear yard</p> <p>54"</p> <p>100% Polyester</p> <p><input type="checkbox"/> FIBER DYED</p> <p><input type="checkbox"/> PILE</p> <p>168 EPI, 53 PPI</p> <p>150D Warp, 600D Fill</p> <p>None</p> <p>PFAS Free</p> <p>SW, Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned.</p>
--	--	---

PHYSICAL PERFORMANCE SPECIFICATIONS

<p>ABRASION RESISTANCE</p> <p>BREAKING STRENGTH</p> <p>BRUSH PILL</p> <p>CROCKING RESISTANCE</p> <p>COLORFASTNESS TO LIGHT</p> <p>SEAM SLIPPAGE</p>	<p>100,000+ Double Rubs*</p> <p>243 Warp, 99 Fill</p> <p>Class 5</p> <p>5 Dry, 5 Wet</p> <p>Class 5</p> <p>84.0 Warp, 83.5 Fill</p>	<p>ASTM D4157-13</p> <p>ASTM D5034-09</p> <p>ASTM D3511</p> <p>AATCC 8-2016</p> <p>AATCC 16.3-2014, Option 3</p> <p>ASTM D4034-92</p>
---	---	---

**Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.*

FLAME RETARDANCY SPECIFICATIONS

<p>CALIFORNIA TECHNICAL BULLETIN 117:13</p> <p>UFAC CLASS I</p> <p>NFPA 260</p>	<p>Pass</p> <p>Pass</p> <p>Pass</p>
---	-------------------------------------

REDUCED ENVIRONMENTAL IMPACT

THIS PRODUCT DOES NOT POSE ANY EXPOSURE RISKS ASSOCIATED WITH THE CHEMICALS IN PROP 65

NO ADDED FLAME RETARDANT CHEMICALS - AB2998 COMPLIANT

NO ADDED ANTI-BACTERIAL / ANTI-MICROBIAL CHEMICALS

LEAD / HEAVY METAL FREE

BPA FREE / TRIS FREE / FORMALDEHYDE FREE

DOES NOT CONTAIN CONFLICT MINERALS



*ACT® Registered Certification Marks